



Product Catalog

Low Volume Irrigation

www.salcodrip.com



TABLE OF CONTENTS

EMITTERS



3



RISERS



7



TUBING



8



FILTRATION



9



SWING PIPE



10



ACCESSORIES



11



TABLE OF CONTENTS

New Products 2

Emitters

Pro-Spec Emitters ½" threaded, ¼" barbed 4

Pro-spec specifications 5

Dirty Water Emitters 6

Risers

IH Risers 7

Tubing

PE 8

PVC and IPS Tubing 8

Filtration 9

Swing Pipe

Swing Pipe and Connectors 10

Accessories 11

Reference

Friction Loss Ref. Charts 14

Warranty Statement

Limited Warranty and Condition of Sales 17



WHAT'S NEW AT SALCO?

Color-matched Tubing

We have the capability to color match our tubing to meet your individual needs. If you have a project that requires a specific color. Please reach out to us and we'll make it happen for you.



NEW PRODUCTS



Highest Quality Drip Zone Kits

Salco now offers the highest quality Drip Zone Kits to meet your installation needs. With industry standards in pressure regulation and durable stainless steel screen. You can be sure this product will perform year over year.

Consider **5 Reasons** why the Pro-Spec Family of Emitters is The Architects Choice!

1 TRUCHECK™ TECHNOLOGY

Salco Trucheck™ technology ensures your emitters will operate at the highest level of performance and efficiency. The only emitter with a positive internal check spring, Pro-Spec PST-CV emitters hold back 9.25' (2,77 m) long after the competitors lose their checking power.

2 EASY INSTALLATION OPTIONS

- ½" FIPT threads
- ¼" x ¼" barbs
- Single or multi-outlet
- Check or non-check models

3 WIDEST OPERATING RANGE

- PC Flow: 0.5, 1, 2, or 4 gph
- Pressure Range: 5 – 65 psi
- Zone Filtration: 100 – 150 Mesh



4 ZERO FLUSH PERFORMANCE

- Minimizes water waste
- Highly efficient hydraulic design
- Run more emitters on a single line.

5 COLOR CONFIGURATIONS

- Color coded and labeled for GPH or camouflaged to blend with the landscape
- Easily identify emitters on the job or in the box.



DOWNLOAD TECH SPECS AT:
www.salcodrip.com

PRO-SPEC EMITTERS

FEATURES

- Fully pressure-compensating zero flush design delivers uniform flow throughout a wide pressure range (5 – 65 psi), regardless of elevation changes and pressure inconsistencies
- Optional Trucheck™ models (PST-CV) include positive internal check spring to hold back 9.25' (2,77 m) of elevated water
- ½" FIPT (PST) or ¼" barbed base (PS) configuration to handle every design situation
- Available in color-coded flow rates of 0.5, 1, 2 and 4 gph, or camouflage colors of desert, granite or mulch
- Flow rate and flow direction are clearly molded into diffuser cap
- Manufactured from UV-inhibited engineering grade plastics – rugged design ensures maximum life span
- Barbed emitters are compatible with PVC or polyethylene tubing. ½" FIPT are compatible with all standard ½" MIPT fittings.



SLV-PST-1 (Threaded)

OPERATING RANGE

PC Flow: 0.5 – 4 gph
 Pressure: 5 – 65 psi
 Filtration: 100-150 mesh

¼" Barbed

WITHOUT TRUCHECK	FLOW RATE	COLOR	INLET
SLV-PS-05	½ gph	Brown	Barbed
SLV-PS-1	1 gph	Black	Barbed
SLV-PS-2	2 gph	Green	Barbed
SLV-PS-4	4 gph	Red	Barbed
SLV-PSG-05	½ gph	Granite Camo	Barbed
SLV-PSG-1	1 gph	Granite Camo	Barbed
SLV-PSG-2	2 gph	Granite Camo	Barbed
SLV-PSG-4	4 gph	Granite Camo	Barbed
SLV-PSD-05	½ gph	Desert Camo	Barbed
SLV-PSD-1	1 gph	Desert Camo	Barbed
SLV-PSD-2	2 gph	Desert Camo	Barbed
SLV-PSD-4	4 gph	Desert Camo	Barbed
SLV-PSM-05	½ gph	Mulch Camo	Barbed
SLV-PSM-1	1 gph	Mulch Camo	Barbed
SLV-PSM-2	2 gph	Mulch Camo	Barbed
SLV-PSM-4	4 gph	Mulch Camo	Barbed
SLV-PSR-05	½ gph	Non-Potable Purple	Barbed
SLV-PSR-1	1 gph	Non-Potable Purple	Barbed
SLV-PSR-2	2 gph	Non-Potable Purple	Barbed
SLV-PSR-4	4 gph	Non-Potable Purple	Barbed

½" Threaded

WITHOUT TRUCHECK	WITH TRUCHECK	FLOW RATE	COLOR	INLET
SLV-PST-05	SLV-PST-CV-05	½ gph	Brown	½" FIPT
SLV-PST-1	SLV-PST-CV-1	1 gph	Black	½" FIPT
SLV-PST-2	SLV-PST-CV-2	2 gph	Green	½" FIPT
SLV-PST-4	SLV-PST-CV-4	4 gph	Red	½" FIPT
SLV-PSTG-05	SLV-PSTG-CV-05	½ gph	Granite Camo	½" FIPT
SLV-PSTG-1	SLV-PSTG-CV-1	1 gph	Granite Camo	½" FIPT
SLV-PSTG-2	SLV-PSTG-CV-2	2 gph	Granite Camo	½" FIPT
SLV-PSTG-4	SLV-PSTG-CV-4	4 gph	Granite Camo	½" FIPT
SLV-PSTD-05	SLV-PSTD-CV-05	½ gph	Desert Camo	½" FIPT
SLV-PSTD-1	SLV-PSTD-CV-1	1 gph	Desert Camo	½" FIPT
SLV-PSTD-2	SLV-PSTD-CV-2	2 gph	Desert Camo	½" FIPT
SLV-PSTD-4	SLV-PSTD-CV-4	4 gph	Desert Camo	½" FIPT
SLV-PSTM-05	SLV-PSTM-CV-05	½ gph	Mulch Camo	½" FIPT
SLV-PSTM-1	SLV-PSTM-CV-1	1 gph	Mulch Camo	½" FIPT
SLV-PSTM-2	SLV-PSTM-CV-2	2 gph	Mulch Camo	½" FIPT
SLV-PSTM-4	SLV-PSTM-CV-4	4 gph	Mulch Camo	½" FIPT
SLV-PSTR-05	SLV-PSTR-CV-05	½ gph	Non-Potable Purple	½" FIPT
SLV-PSTR-1	SLV-PSTR-CV-1	1 gph	Non-Potable Purple	½" FIPT
SLV-PSTR-2	SLV-PSTR-CV-2	2 gph	Non-Potable Purple	½" FIPT
SLV-PSTR-4	SLV-PSTR-CV-4	4 gph	Non-Potable Purple	½" FIPT



DOWNLOAD TECH SPECS AT:
www.salcoirrigation.com

PRO-SPEC SPECIFICATIONS (MULTI OUTLET)

TYPE	MODEL	FLOW RATE	COLOR
Barbed	SLV-PS6-05	½ gph per outlet	Brown
Barbed	SLV-PS6-1	1 gph per outlet	Gray
Barbed	SLV-PS6-2	2 gph per outlet	Dark Green
Barbed	SLV-PS6-4	4 gph per outlet	Red
½" FIPT	SLV-PS6T-05	½ gph per outlet	Brown
½" FIPT	SLV-PS6T-1	1 gph per outlet	Gray
½" FIPT	SLV-PS6T-2	2 gph per outlet	Dark Green
½" FIPT	SLV-PS6T-4	4 gph per outlet	Red



MULTI-OUTLET MODEL SPECIFICATIONS



PC6 (Barbed)



PC6T (Threaded)

SELF CLEANING MODELS			
TYPE	MODEL	FLOW RATE	COLOR
Barbed	SLV-PC6-05	½ gph per Outlet	Tan
Barbed	SLV-PC6-1	1 gph per Outlet	Black
Barbed	SLV-PC6-2	2 gph per Outlet	Light Green
Threaded	SLV-PC6T-05	½ gph per Outlet	Tan
Threaded	SLV-PC6T-1	1 gph per Outlet	Black
Threaded	SLV-PC6T-2	2 gph per Outlet	Ligh Green

MULTI OUTLET DRIP MANIFOLD

- Outlet flow can be varied with an emitter at the end of distribution tubing
- Available in ½" FIPT or barbed inlet
- Allows water to be directed to as many as six different locations
- Outlets can be opened/closed as necessary using part SLV-PC6-C
- Unrestricted flow through outlets indicated by blue color



MODELS

SLV-DMT-6 (Threaded)
SLV-DM-6 (Barbed)

D2 DIRTY WATER EMITTERS

D2 EMITTERS D2 SERIES PASSES 2X THE AMOUNT OF DIRT COMPARED WITH TRADITIONAL EMITTERS!

ALL MODELS FEATURE

- Ideal for reclaimed and well water applications.
- Fully pressure compensating design delivers uniform flow throughout a wide pressure range, (5-45 psi; .33 bars - 3 bars) regardless of elevation changes and pressure inconsistencies.
- Available in flow rates of 0.5, 1, & 2 gph.
- Flow rates and flush options are color coded.
- Rugged design. Each emitter is manufactured from UV-inhibited engineering grade plastics to ensure maximum life span.
- Barbed emitters are compatible with PVC or polyethylene tubing. ½" FIPT models are compatible with all standard ½" MIPT fittings.

SINGLE OUTLET FEATURES

- ½" FIPT or barbed base configuration to handle every design situation*
- Available in self-cleaning or zero-flush configurations
- Multi-Outlet Features
- ½" FIPT or barbed base and 6 barbed outlets to handle every design situation
- Unused outlets must be capped using outlet caps (part #PC6-C)

OPERATING RANGE

PC Flow: 0.5 – 2 gph [Single Outlet]

0.5 – 2 gph x 6 [Multi-Outlet]

Pressure: 5 – 45 psi

Filtration: 80 – 150 Mesh



SINGLE OUTLET MODEL SPECIFICATIONS

MODELS							
Type	Self Cleaning	Color Code	Zero Flush	Color Code	Flow Rate	Inlet	Outlet
Threaded	SLV-PCRT-05	Tan	SLV-PCRTZ-05	Brown	½ GPH	½" FIPT	1/8" Barbed
	SLV-PCRT-1	Black	SLV-PCRTZ-1	Gray	1 GPH	½" FIPT	1/8" Barbed
	SLV-PCRT-2	Lt. Green	SLV-PCRTZ-2	Dk. Green	2 GPH	½" FIPT	1/8" Barbed
Barbed	SLV-PCR-05	Tan	SLV-PCRZ-05	Brown	½ GPH	¼" Barbed	1/8" Barbed
	SLV-PCR-1	Black	SLV-PCRZ-1	Gray	1 GPH	¼" Barbed	1/8" Barbed
Micro	SLV-PCR-2	Lt. Green	SLV-PCRZ-2	Dk. Green	2 GPH	¼" Barbed	1/8" Barbed
Bubblers	SLV-PCC-05	Tan	SLV-PCCZ-05	Brown	½ GPH	¼" Barbed	Diffused
	SLV-PCC-1	Black	SLV-PCCZ-1	Gray	1 GPH	¼" Barbed	Diffused
	SLV-PCC-2	Lt. Green	SLV-PCCZ-2	Dk. Green	2 GPH	¼" Barbed	Diffused

IH-SERIES RISERS

H-SERIES RISERS

FEATURES

- Pre-assembled with two ½" MIPT UVR male adapters
- Accepts any ½" FIPT emitter
- Cost less preassembled than purchased separately in parts
- Ideal for slope applications
- Pre-assembly reduces installation cost by up to 50%
- On grade or below grade installation
- Custom lengths available
- Also available pre-assembled with PST emitters

OPERATING RANGE

Max Flow: 7 gpm
Max Pressure: 60 psi



RISER ASSEMBLIES PRE-ASSEMBLED WITH SALCO PST EMITTERS

MODEL	ADAPTER COLOR
SLV-PVC-y-ACLxx	Black
SLV-PVC-y-M-ACLxx	Black
SLV-PVC-y-D-ACLxx	Black
SLV-PVC-y-G-ACLxx	Black
SLV-PVC-y-R-ACLxx	Black

y = Emitter flow rate ("050" = ½ gph, "1" = 1 gph, "2" = 2 gph, and "4" = 4 gph)
xx = Length of riser ("12" or "18" or "24")

NO EMITTER RISER ASSEMBLIES PRE-ASSEMBLED RISERS WITH 2 MALE ADAPTERS

MODEL	ADAPTER COLOR
SLV-PVC-ACLxx	Black
SLV-PVC-M-ACLxx	Black
SLV-PVC-D-ACLxx	Black
SLV-PVC-G-ACLxx	Black
SLV-PVC-R-ACLxx	Black

xx = Length of riser ("12" or "18" or "24")



TUBING

Distribution Tubing



POLYETHYLENE MICRO TUBING

MODEL	DESCRIPTION	QUANTITY
SLV-PE-125-063-3500	0.125" x 0.063"	3,500' coil
SLV-PE-128-076-3500	0.128" x 0.076"	3,500' coil
SLV-PE-176-105-2000	0.176" x 0.105"	2,000' coil
SLV-PE-187-125-100	0.187" x 0.125"	100' coil
SLV-PE-187-125-1000	0.187" x 0.125"	1,000' coil
SLV-PE-188-128-3000	0.188" x 0.128"	3,000' coil
SLV-PE-220-160-100	0.220" x 0.160"	100' coil
SLV-PE-220-160-1000	0.220" x 0.160"	1,000' coil
SLV-PE-220-160-2500	0.220" x 0.160"	2,500' coil
SLV-PE-225-155-2500	0.225" x 0.155"	2,500' coil
SLV-PE-250-125-2000	0.250" x 0.125"	2,000' coil
SLV-PE-250-170-100	0.250" x 0.170"	100' coil
SLV-PE-250-170-1000	0.250" x 0.170"	1,000' coil
SLV-PE-250-170-2000	0.250" x 0.170"	2,000' coil
SLV-PE-272-188-1500	0.272" x 0.188"	1,500' coil
SLV-PE-275-210-1500	0.275" x 0.210"	1,500' coil
SLV-PE-307-250-1000	0.307" x 0.250"	1,000' coil
SLV-PE-350-250-500	0.350" x 0.250"	500' coil
SLV-PE-350-250-1000	0.350" x 0.250"	1,000' coil
SLV-PE-375-250-750	0.375" x 0.250"	750' coil
SLV-PE-455-375-1000	0.455" x 0.375"	1,000' coil
SLV-PE-455-375-CL24	0.455" x 0.375" x 24"	24" cut

VINYL MICRO TUBING

MODEL	DESCRIPTION	QUANTITY
SLV-PVC-187-125-100	0.187" x 0.125"	100' coil
SLV-PVC-187-125-2000	0.187" x 0.125"	2,000' coil
SLV-PVC-220-160-100	0.220" x 0.160"	100' coil
SLV-PVC-220-160-1000	0.220" x 0.160"	1,000' coil
SLV-PVC-220-160-2500	0.220" x 0.160"	2,500' coil
SLV-PVC-250-170-100	0.250" x 0.170"	100' coil
SLV-PVC-250-170-1000	0.250" x 0.170"	1,000' coil
SLV-PVC-250-170-2000	0.250" x 0.170"	2,000' coil

Flexible IPS Hose

FLEXIBLE IPS HOSE



MODEL	DESCRIPTION	QUANTITY
SLV-PVC-IPS-050-100	½" IPS	100' coil
SLV-PVC-IPS-050-200	½" IPS	200' coil
SLV-PVC-IPS-075-100	¾" IPS	100' coil
SLV-PVC-IPS-075-200	¾" IPS	200' coil
SLV-PVC-IPS-100-100	1" IPS	100' coil

Supply Tubing

SUPRA FLEX™ POLY SUPPLY TUBING

MODEL	DESCRIPTION	QUANTITY
SLV-PE-620-520-100	.620" x .520"	100' coil
SLV-PE-620-520-500	.620" x .520"	500' coil
SLV-PE-620-520-1000	.620" x .520"	1,000' coil
SLV-PE-700-600-100	.700" x .600"	100' coil
SLV-PE-700-600-500	.700" x .600"	500' coil
SLV-PE-700-600-1000	.700" x .600"	1,000' coil
SLV-PE-700-600-CL24	.700" x .600"	24" cut length
SLV-PE-710-620-100	.710" x .620"	100' coil
SLV-PE-710-620-500	.710" x .620"	500' coil
SLV-PE-710-620-1000	.710" x .620"	1,000' coil
SLV-PE-940-820-100	.940" x .820"	100' coil
SLV-PE-940-820-500	.940" x .820"	500' coil
SLV-PE-940-820-1000	.940" x .820"	1,000' coil
SLV-PE-1174-1050-250	1.174" x 1.050"	250' coil
SLV-PE-1200-1060-250	1.200" x 1.060"	250' coil

A/R Flex PVC TuBing

For Use With Recycled/Reclaimed Water

MODEL	DESCRIPTION	QUANTITY
SLV-PVC-AR-050-500	½" Irrigation Size Hose (3/8" IPS)	500' Coil
SLV-PVC-AR-IPS-050-200	½" IPS	200' Coil
SLV-PVC-AR-IPS-075-200	¾" IPS	200' Coil
SLV-PVC-AR-IPS-100-100	1" IPS	100' Coil



NON-ALGAEICIDE FLEXIBLE IPS HOSE

MODEL	DESCRIPTION	QUANTITY
SLV-PVC-NA-IPS-050-CL24	½" IPS	24" cut length
SLV-PVC-NA-IPS-050-CL30	½" IPS	30" cut length
SLV-PVC-NA-IPS-050-CL36	½" IPS	36" cut length
SLV-PVC-NA-IPS-050-CL48	½" IPS	48" cut length
SLV-PVC-NA-IPS-050-CL60	½" IPS	60" cut length
SLV-PVC-NA-IPS-075-CL24	¾" IPS	24" cut length
SLV-PVC-NA-IPS-075-CL30	¾" IPS	30" cut length
SLV-PVC-NA-IPS-075-CL36	¾" IPS	24" cut length
SLV-PVC-NA-IPS-075-CL42	¾" IPS	42" cut length
SLV-PVC-NA-IPS-075-CL48	¾" IPS	48" cut length
SLV-PVC-NA-IPS-075-CL60	¾" IPS	60" cut length
SLV-PVC-NA-IPS-100-CL36	1" IPS	36" cut length
SLV-PVC-NA-IPS-100-CL60	1" IPS	60" cut length

FILTERS

WYE FILTERS



FEATURES

- Manufactured from ABS
- 150 mesh stainless steel screen
- Non-migrating seals eliminate water blow-by

OPERATING RANGE

Flow: Max of 20 GPM
Pressure: 0 - 150 PSI
Filtration: 150 Mesh
(others available)

MODEL SPECIFICATION

MODEL	DESCRIPTION
SLV-HYS-075	3/4" Inlet x 3/4" Outlet
SLV-HYSF-075	3/4" Inlet x 3/4" Outlet w/Manual Flush Valve
SLV-HYS-100	1" Inlet x 3/4" Outlet
SLV-HYSF-100	1" Inlet x 3/4" Outlet w/ Manual Flush Valve

Drip Zone Kits



MODEL	DESCRIPTION
SLV-FR-075-25	3/4" Inlet/Outlet Pressure Regulated to 25 PSI
SLV-FR-075-40	3/4" Inlet/Outlet Pressure Regulated to 40 PSI
SLV-FR-100-25	1" Inlet x 3/4" Outlet Pressure Regulated to 25 PSI
SLV-FR-100-40	1" Inlet x 3/4" Outlet Pressure Regulated to 40 PSI

FEATURES

- Highest quality components with stainless steel filter screen, flush cap and industry standard pressure regulator.
- Flow range compatible with most drip systems.

SWING PIPE

SWING PIPE

FEATURES

- Inside diameter: .49"
- 100' (30,0 m) stackable coils, marked in 12" increments SPC-100 – High-Pressure Swing Pipe
- Engineered for high pressures, up to 150 psi
- Quick and easy installation SPCX-100 – Super Flex Swing Pipe
- Contractor-preferred maximum flexibility without kinking
- Textured surface is easy to grip even when wet
- Engineered for pressures up to 80 psi

MODELS

SPC-10	High-Pressure Swing Pipe
SPCX-100	Super Flex Swing Pipe



SWING ASSEMBLIES

FEATURES

- Marlex™ ells can be adjusted to virtually any configuration, leak free
- "3L" configuration has a Marlex™ ell on one end – ideal for use with horizontally mounted tees
- "4L" configuration has Marlex™ ells on both ends for maximum versatility with vertically mounted tees
- High pressure tested to over 100 PSI

MODELS	LENGTH	INLET/OUTLET
SPSA-65050-3L	6"	1/2" x 1/2"
SPSA-65075-3L	6"	1/2" x 3/4"
SPSA-125050-3L	12"	1/2" x 1/2"
SPSA-125075-3L	12"	1/2" x 3/4"
SPSA-127575-3L	12"	3/4" x 3/4"
SPSA-65050-4L	6"	1/2" x 1/2"
SPSA-65075-4L	6"	1/2" x 3/4"
SPSA-125050-4L	12"	1/2" x 1/2"
SPSA-125075-4L	12"	1/2" x 3/4"
SPSA-127575-4L	12"	3/4" x 3/4"

*Spray not included



FITTINGS

FEATURES

- Easy twist-in insertion without use of glue or clamps
- Multiple barbs – prevents barb blow-out
- Hard acetal thermoplastic for sharper barbs



SASBA-050



SASBA-075



SASB-TEE



SASB-COUP

SASB-ELBOW-075



SASB-ELBOW-050



MODELS

SASB-COUP	1/2" Barb x 1/2" Barb Coupling
SASBA-050	1/2" (15/21) M NPT x 1/2" Barb Adapter
SASBA-075	3/4" (20/27) M NPT x 1/2" Barb Adapter
SASB-ELBOW-050	1/2" (15/21) M NPT x 1/2" Barb Elbow
SASB-ELBOW-075	3/4" (20/27) M NPT x 1/2" Barb Elbow
SASB-TEE	1/2" Barb x 1/2" Barb Tee

DOWNLOAD TECH SPECS AT:
www.salcodrip.com

BUG CAPS



FEATURES

- Prevents insect intrusion
- An added defense against foreign particles
- Available for tubing with ODs of 0.187", 0.220"-0.270" and 0.300"

MODELS

SLV-EOCV-125	Bug cap for 0.187" OD tubing & 1/8" barbs
SLV-EOCV-220	Bug cap for 0.220" - 0.270" OD tubing & 1/4" barbs
SLV-EOCV-300	Bug cap for 0.300" OD tubing

EMITTER ACCESS SLEEVE



FEATURES

- Provides convenient access to subsurface emitters while protecting against vandalism
- Slotted body facilitates installation of distribution tubing
- Rugged, UV-resistant thermoplastic construction
- 12" tall, 4.75" wide

MODELS

SLV-DAS-8	Emitter access sleeve (black)
SLV-DAS-8R	Emitter access sleeve (reclaimed purple)

RIGID RISERS

Rigid Risers are used throughout a micro irrigation system in conjunction with micro emitters and fittings.

FEATURES

- Rigid Risers are available in 4 lengths
- Rigid Risers in plain, barbed, threaded and 1/2" MNPT configuration
- UV stabilized materials for long life

MODEL SPECIFICATION

SLV-50115	Riser 6" Plain
SLV-50125	Riser 8" Plain
SLV-50135	Riser 12" Plain
SLV-50145	Riser 18" Plain

APPLICATIONS

Rigid Risers accept all "Quick" thread and 10-32 UNF products (i.e. drippers, sprays and sprinklers).

ACCESSORIES

PUNCH TOOLS

FEATURES

- The toughest, most rugged punch tool on the market
- Made from stainless steel to ensure durability and longevity
- Will punch any hose from 3/8" to 1"
- Replacable and adjustable punch tip

SLV-HP-125
SLV-HPT-05
(Replacement Tip)



GOOF PLUGS

FEATURES

- Plugs misplaced or unneeded punctures in supply tubing
- Two sided, plugs 0.187" (1/8") and 0.250" (1/4") size holes

MODELS

SLV-42325	Rack of 10 Goof Plugs
SLV-GFP	Goof Plug



AUTOMATIC FLUSH VALVE

FEATURES

- Automatic and manual flushing
- Easy to use 3/4" hose thread with drip-tight washer
- Highly visible color coded flow indicator
- Unique two-piece button allows manual flushing in hot temperatures



MODELS

SLV-AFV-075L	Automatic flush valve, low flow
SLV-AFV-075H	Automatic flush valve, high flow

PVC IRRIGATION HOSE ADAPTER

FEATURES

- Adapts a 1/2" IPS slip to 1/2" irrigation size
- Made of high impact PVC to endure the harshest conditions
- Solvent welds using standard methods
- For use with Salco PVC flex hose



MODELS

SLV-IHA-050	PVC Irrigation Hose Adapter, converts 1/2" IPS to 3/8"
-------------	--

STAKES

TUBING STAKES

- DTS-20-400 & DTS-20-400B (compatible with 1/8" to 1/4" tubing) are made from UVR Plastic and accept any manufacturer's distribution tubing
- DTS-30-750 (compatible with 1/8" to 1/4" tubing) & DTS-140-900 (compatible with 1/2" to 1" tubing) are PVC-coated galvanized wire to ensure rust resistance
- Ideal for high profile applications



DOWNLOAD TECH SPECS AT:
www.salcodrip.com

ACCESSORIES

PVC MALE ADAPTER

- Made of high impact PVC to endure the harshest conditions
- Solvent welds using standard methods
- Available in black, reclaimed purple and desert camo (except adapter)
- Perfect for use with Salco's PST, PCCT, and PCRT series mitters
- Compatible with any ½" female threaded component



MODELS

SLV-436-073B	½" MIPT x ½" Irrigation Size 3/8" IPS (Black)
SLV-436-073R	½" MIPT x ½" Irrigation Size 3/8" IPS (Reclaimed Purple)
SLV-436-005B	½" MIPT x ½" IPS (Black)
SLV-436-005R	½" MIPT x ½" IPS (Reclaimed Purple)

17MM FITTINGS

FEATURES

- Easy insertion without use of glue or clamps
- Multiple barbs – prevents blow-outs
- Hard thermoplastic material for sharper barbs
- Maximum 50 psi (3,4 bar) operation pressure
- Compatible with all 17 mm brands

MODELS

SLV-ICOUP-17MM	17 mm Coupling
SLV-IELBOW-17MM	17 mm Elbow
SLV-ITEE-17MM	17 mm Tee
SLV-IMAD-050-17MM	17 mm ½" MIPT Adapter
SLV-IMAD-075-17MM	17 mm ¾" MIPT Adapter



SLV-ICOUP-17MM



SLV-IMAD-050-17MM



LV-IMAD-075-17MM



SLV-ITEE-17MM



SLV-IELBOW-17MM

EMITTER OUTLET CAPS

Plugs unused 1/8" barbed emitter outlets

- For use with PC6, PC6T, PC6Z, PC6TZ, DM6 and DM6T

MODELS

SLV-PC6-C	Emitter Outlet Cap
-----------	--------------------



REFERENCE

REFERENCE

POLYETHYLENE (PE) SDR PRESSURE RATED TUBE

C = 140

Loss per 100' of pipe (psi/100')

Size I.D.	½"		¾"		1"		1 ¼"		1 ½"		2"		2 ½"		3"		4"		
	0.622		0.824		1.049		1.380		1.610		2.067		2.469		3.068		4.026		
Flow gpm	Velocity fps	psi loss	Velocity fps	psi loss	Velocity fps	psi loss	Velocity fps	psi loss	Velocity fps	psi loss	Velocity fps	psi loss	Velocity fps	psi loss	Velocity fps	psi loss	Velocity fps	psi loss	
1	1.06	0.488	0.60	0.124	0.37	0.038	0.21	0.010	0.16	0.005	0.01	0.001	0.07	0.001	0.04	0.000	0.03	0.000	
2	2.11	1.759	1.20	0.448	0.74	0.138	0.43	0.036	0.32	0.017	0.19	0.003	0.13	0.002	0.09	0.001	0.05	0.000	
3	3.17	3.723	1.80	0.948	1.11	0.293	0.64	0.077	0.47	0.036	0.29	0.007	0.20	0.005	0.13	0.002	0.08	0.000	
4	4.22	6.340	2.41	1.614	1.48	0.499	0.86	0.131	0.63	0.062	0.38	0.012	0.27	0.008	0.17	0.003	0.10	0.001	
5	5.28	9.580	3.01	2.438	1.86	0.753	1.07	0.198	0.79	0.094	0.48	0.018	0.34	0.012	0.22	0.004	0.13	0.001	
6	6.34	13.422	3.61	3.417	2.23	1.055	1.29	0.278	0.95	0.131	0.57	0.025	0.40	0.016	0.26	0.006	0.15	0.002	
7	7.39	17.852	4.21	4.544	2.60	1.404	1.50	0.369	1.10	0.175	0.67	0.034	0.47	0.022	0.30	0.008	0.18	0.002	
8	8.45	22.854	4.81	5.817	2.97	1.797	1.72	0.473	1.26	0.223	0.76	0.043	0.54	0.028	0.35	0.010	0.20	0.003	
9	9.50	28.418	5.41	7.234	3.34	2.235	1.93	0.588	1.42	0.278	0.86	0.053	0.60	0.035	0.39	0.012	0.23	0.003	
10	10.56	34.534	6.02	8.790	3.71	2.716	2.15	0.715	1.58	0.338	0.96	0.065	0.67	0.042	0.43	0.015	0.25	0.004	
11	11.61	41.193	6.62	10.485	4.08	3.239	2.36	0.853	1.73	0.403	1.05	0.077	0.74	0.050	0.48	0.017	0.28	0.005	
12	12.67	48.388	7.22	12.317	4.45	3.805	2.57	1.001	1.89	0.473	1.15	0.091	0.80	0.059	0.52	0.021	0.30	0.005	
14	14.78	64.355	8.42	16.381	5.20	5.061	3.00	1.332	2.21	0.629	1.34	0.121	0.94	0.079	0.61	0.027	0.35	0.007	
16	16.89	82.389	9.63	20.972	5.94	6.479	3.43	1.705	2.52	0.805	1.53	0.155	1.07	0.101	0.69	0.035	0.40	0.009	
18	19.01	102.448	10.83	26.078	6.68	8.056	3.86	2.120	2.84	1.001	1.72	0.193	1.21	0.126	0.78	0.043	0.45	0.012	
20	21.12	124.496	12.03	31.690	7.42	9.790	4.29	2.577	3.15	1.217	1.91	0.234	1.34	0.153	0.87	0.053	0.50	0.014	
22			13.24	37.800	8.17	11.677	4.72	3.074	3.47	1.452	2.10	0.279	1.47	0.182	0.95	0.063	0.55	0.017	
24			14.44	44.402	8.91	13.717	5.15	3.610	3.78	1.705	2.29	0.328	1.61	0.214	1.04	0.074	0.60	0.020	
26			15.64	51.489	9.65	15.906	5.58	4.187	4.01	1.977	2.49	0.380	1.74	0.248	1.13	0.086	0.66	0.023	
28			16.85	59.055	10.39	18.243	6.01	4.802	4.41	2.268	2.68	0.436	1.88	0.284	1.22	0.098	0.71	0.026	
30			18.05	67.094	11.14	20.727	6.44	5.455	4.73	2.577	2.87	0.495	2.01	0.323	1.30	0.112	0.76	0.030	
35			21.06	89.236	12.99	27.567	7.51	7.256	5.52	3.427	3.35	0.659	2.35	0.430	1.52	0.149	0.88	0.040	
40					14.85	35.291	8.58	9.289	6.30	4.387	3.82	0.843	2.68	0.550	1.74	0.190	1.01	0.051	
45					16.71	43.883	9.65	11.550	7.09	5.455	4.30	1.049	3.02	0.684	1.95	0.237	1.13	0.063	
50					18.56	53.328	10.73	14.036	7.88	6.630	4.78	1.274	3.35	0.831	2.17	0.288	1.26	0.077	
55					20.42	63.610	11.80	16.743	8.67	7.908	5.26	1.520	3.69	0.992	2.39	0.343	1.39	0.091	
60							12.87	19.667	9.46	9.289	5.74	1.785	4.02	1.165	2.60	0.403	1.51	0.107	
65							13.94	22.806	10.24	10.772	6.21	2.070	4.36	1.351	2.82	0.468	1.64	0.125	
70							15.02	26.157	11.03	12.354	6.69	2.375	4.69	1.549	3.04	0.536	1.76	0.143	
75							16.09	29.718	11.82	14.036	7.17	2.698	5.03	1.760	3.25	0.609	1.89	0.162	
80							17.16	33.487	12.61	15.816	7.65	3.040	5.36	1.983	3.47	0.686	2.02	0.183	
85							18.23	37.461	13.40	17.693	8.13	3.401	5.70	2.219	3.69	0.768	2.14	0.205	
90									14.18	19.667	8.61	3.780	6.03	2.466	3.91	0.854	2.27	0.227	
95									14.97	21.736	9.08	4.178	6.37	2.726	4.12	0.943	2.39	0.251	
100									15.76	23.899	9.56	4.594	6.70	2.997	4.34	1.037	2.52	0.276	
110									17.34	28.508	10.52	5.480	7.37	3.575	4.77	1.237	2.77	0.330	
120											11.47	6.437	8.04	4.199	5.21	1.453	3.02	0.387	
130											12.43	7.464	8.71	4.870	5.64	1.685	3.28	0.449	
140											13.39	8.561	9.38	5.585	6.08	1.933	3.53	0.515	
150											14.34	9.726	10.05	6.346	6.51	2.196	3.78	0.585	
160											15.30	10.960	10.72	7.150	6.94	2.475	4.03	0.659	
170											16.25	12.261	11.39	7.999	7.38	2.768	4.28	0.738	
180														12.06	8.891	7.81	3.077	4.54	0.820
190														12.73	9.827	8.25	3.401	4.79	0.906
200														13.40	10.805	8.68	3.740	5.04	0.996
225														15.08	13.435	9.76	4.650	5.67	1.239
250														16.75	16.327	10.85	5.651	6.30	1.505
275																11.93	6.740	6.93	1.796
300																13.02	7.917	7.56	2.109
325																14.10	9.181	8.19	2.446
350																15.19	10.530	8.82	2.806
375																16.27	11.964	9.45	3.187
400																		10.08	3.592
425																		10.71	4.018
450																		11.34	4.466
475																		11.97	4.936
500																		12.60	5.427
550																		13.86	6.474
600																		15.12	7.604

Shading indicates velocities over 5 fps (not recommended).

Conditions of Sale and Limited Warranty

Salco Products warrants to its trade customers that its products will be free from original defects in material and workmanship for a period of three years from date of purchase.

Within the warranty period and upon due notice and delivery of defective products to Salco, Salco agrees to repair or replace only product determined by Salco to be defective. In no event shall Salco be liable for payment of any charges or expenses other than the cost of performing its obligation to repair or replace at Salco's sole discretion in accordance with this basic commercial warranty. Misuse, neglect or unauthorized repairs shall void this warranty. The warranty is expressly limited to Salco Products only.

Salco Products shall not be liable for incidental or consequential damages of any nature. Salco Products sole liability shall be for the repair or replacement of defective parts at Salco's sole discretion pursuant with this warranty.

Salco makes no other warranties expressed or implied. No agent, distributor, representative, or anyone else has the authority to waive, alter, or add to the printed provisions of this warranty, to make any representation or warranty not contained herein, or to extend this warranty to anyone other than the original user. Salco reserves the right to redesign or modify its products without incurring further liability.

In order to obtain the benefits of this warranty, the owner must contact the Salco Products Customer Care Department as soon as possible after discovery of the defect but, in no event, later than the expiration of the warranty provided in this warranty. Upon receipt of this communication, Salco Products will promptly notify the owner of the address to which the defective item may be shipped. The owner shall then ship the item, freight prepaid, to the address indicated, together with a "RETURN GOODS AUTHORIZATION" code obtained from the Customer Care Department and a brief description of the problem(s) encountered with the item. Unauthorized returns will not be accepted.

Order Acceptance:

Salco Products reserves the right to accept or reject any order. Possession of Salco Product's catalog or price list does not constitute an offer to sell nor a right to purchase.

Credit:

A signed Salco Products credit application is required prior to an account being reviewed for credit approval or discount eligibility. COD may be requested for accounts with credit applications in process or otherwise deemed.

Terms:

Approved credit applications will receive Net 30 day unless specified otherwise. Past due thereafter. Accounts may be placed on hold or terms revoked due to unsatisfactory payment.

Delivery:

Delivery estimates are made in good faith and are subject to government restrictions, failure by our suppliers to deliver, fires, strikes or other causes beyond our control.

Shortages:

Claims for shortages or errors in shipping must be in writing and will not be recognized after seven days from date of delivery.

Pricing:

We reserve the right to change prices without notice. We will dispatch goods at the current price. Customers may request confirmation of current prices when ordering.

Salco Products
1930 South Rochester Ave. Unit 111
Ontario, CA 91761
Toll Free: 1-855-SALCO4U (1-855-725-2648)
Phone: 909-937-3923 • Fax: 909-937-2017
www.salcodrip.com

Water **smarter**

www.salcodrip.com



Toll Free: 1-855-SALCO4U (1-855-725-2648)

Phone: 909-937-3923

Fax: 909-937-2017

Salco Products

1930 South Rochester Ave. Unit 111

Ontario, CA 91761